

UNIT #719

One (1) 250 horsepower Superior Mohawk firetube package boiler originally constructed in 1987 in strict accordance with the ASME Code, Section I for a design pressure of 150 PSI steam and bears National Board stampings. The boiler is capable of producing 8,625 PPH and is equipped with a Gordon Piatt natural gas and #2 oil fired forced draft burner complete with Honeywell flame management control system.

Valving trim and ancillary equipment includes, but is not limited to the following;

Water columns with primary and secondary low water cut off, pump control and low water alarms, gauge glass , gauge cocks and drain valves.

Safety, Blowdown, Feedwater stop and check valves.

Forced draft fan with 25 HP TEFC motor and starter.

Honeywell BC 7000 diagnostic burner management system, relays, indicating Lights, Limits and Alarm horn.

Single point 480volt-power connection with 120volt-control transformer.

Fuel valving and controls meeting FM, IRI standards

Connections:

Steam: 6" 300# flange

Water: 2"

Gas: 2.5"

Blow Down: 2"

Electric: 480v 3ph 60 Hz.

Dimensions:

Length: 17' 10"

Width: 7' 6"

Height: 8'6"

Shipping Weight: 23,000 lbs.

This unit is offered completely remanufactured. This unit has been test fired at our facilities. The boiler is offered with a one (1) year parts and motors warranty (less labor) and the pressure vessel is guaranteed to pass an ASME inspection.

Availability of this unit is 1 week from date of order with 50% deposit.